



**Product Specifications**

<b>Construction</b>	Patterned Loop
<b>Backing</b>	Nexus® Modular
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	APEX SDP® Polyester
<b>Face Weight</b>	16 oz./sy (543 grams/m2)
<b>Pile Density</b>	5872 oz./y3 (217.74 kg/m3)
<b>Pattern Repeat</b>	24.00" (w) x 24.00" (l) approx. (60.96cm x 60.96cm)
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Standard Size</b>	24" x 24" approx. (60.96cm x 60.96cm)
<b>Standard Adhesive</b>	Commercialon Premium Modular Adhesive
<b>Optional Adhesive</b>	TileTabs
<b>Standard Warranties</b>	<b>Nexus Modular Commercialon Adhesive for Modular Carpet &amp; LVT APEX® SDP Polyester Fiber</b>
<b>Optional Warranties</b>	<b>Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs</b>










**Special Technologies**

**Environmental Specifications & Tests**

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	75.3%
<b>Flooring Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less then 450.0 flaming (ASTM E 662)
<b>Static Test</b>	Less then 3.5 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

**Installation Methods:** Brick, Quarter Turn, Monolithic, Ashlar

Colorways

 3410 Symmetry	 3411 Geometric	 3412 Streamline	 3413 Distinction	 3414 Architectu..	 3415 Neo Gothic
 3416 Individual	 3417 Aristocratic	 3418 Angularity			