

Error

Source: Unable to
'tiles/6544B_3660

7.472 d6d9b3a2/757/1

Product Specifications

Construction	Patterned Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	15 oz./sy (509 grams/m ²)
Pile Density	4820 oz./y ³ (178.73 kg/m ³)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back APEX® SDP Polyester Fiber
Optional Warranties	iLoc® Backing

Special Technologies

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



3655 Obstacle



3656 Impede




3657 Besiege



3658 Stoppage




3659 Barricade



3660 Road Block



3661 Closure



3662 Obstruction



3663 Fortify