



## Product Specifications

<b>Construction</b>	Textured Loop
<b>Backing</b>	Nexus® Modular
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	APEX SDP® Polyester
<b>Face Weight</b>	15 oz./sy (509 grams/m <sup>2</sup> )
<b>Pile Density</b>	8627 oz./y <sup>3</sup> (319.89 kg/m <sup>3</sup> )
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Standard Size</b>	12" x 48" approx. (30.48cm x 121.92cm)
<b>Standard Adhesive</b>	Commercialon Premium Modular Adhesive
<b>Optional Adhesive</b>	TileTabs
<b>Standard Warranties</b>	<b>Nexus Modular Commercialon Adhesive for Modular Carpet &amp; LVT APEX® SDP Polyester Fiber</b>
<b>Optional Warranties</b>	<b>Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs</b>


## Special Technologies

### Environmental Specifications & Tests


<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	76.4%
<b>Flooring Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450.0 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3.5 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

**Installation Methods:** Herringbone, Ashlar


## Colorways




2972 Data Link



2973 Connection



2974 Application




2975 Nature




2976 Packet




2977 Session



3165 Satellite




3166 Router



3167 Coaxial



3168 Hardware



3169 Gateway



3170 Modem