

Error

Source: Unable to
'tiles/3094B_3204

7.472 2d0990f8/659/21

Product Specifications


Construction	Textured Loop
Backing	Woven Polypropylene (HP)
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	18 oz./sy (610 grams/m2)
Pile Density	5354 oz./y3 (198.53 kg/m3)
Pattern Repeat	24.00" (w) x 36.00" (l) approx. (60.96cm x 91.44cm)
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	APEX® SDP Polyester Fiber
Optional Warranties	iLoc® Backing

Special Technologies

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less then 450.0 flaming (ASTM E 662)
Static Test	Less then 3.0 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways



3200 Cloud



3201 Smoke



3202 Tortilla



3203 Oyster



3204 Fossil




3205 Iron



3206 Hazlenut



3207 Parchment




3208 Flint



3209 Indigo



3210 Charcoal



3211 Denim



3212 Hickory



3213 Peanut



3214 Granola