Fast Break | 7060T

Installation Methods: Brick, Quarter Turn, Monolithic, Ashlar

Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	15 oz./sy (509 grams/m2)
Pile Density	5133 oz./y3 (190.33 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	**Nexus Modular** **Commercialon Adhesive for Modular Carpet & LVT** **APEX® SDP Polyester Fiber**
Optional Warranties	**Commercialon High Moisture Adhesive for Modular Carpet and LVT** **Tile Tabs**

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	76.4%
Flooring Radiant Panel	Class 1
Smoke Density	Less then 450.0 flaming (ASTM E 662)
Static Test	Less then 3.5 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

2144 Buzzer Be...

2145 Alley-Oop

2146 Give-and-...

2147 Coast-to-...

2148 Run-and-...

2149 Lay-Up

2150 Slam Dunk

2151 Dunk Shot

2152 Three Poi...