

Error

Source: Unable to
'tiles/6645B_3670

7.472 9a0a2caf/764/16

Product Specifications


Construction	Patterned Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	15 oz./sy (509 grams/m ²)
Pile Density	4063 oz./y ³ (150.66 kg/m ³)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back APEX® SDP Polyester Fiber
Optional Warranties	iLoc® Backing

Special Technologies

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450.0 flaming (ASTM E 662)
Static Test	Less than 3.5 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




3664 Backward ...




3665 Blackboard




3666 Pruning




3667 Task




3668 Heuristics




3669 Environm...



3670 Automata



3671 Logic



3672 Neural Ne...