





## **Product Specifications**

Construction	Textured Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	26 oz./sy (882 grams/m2)
Pile Density	7488 oz./y3 (277.66 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back APEX® SDP Polyester Fiber
<b>Optional Warranties</b>	iLoc® Backing

## **Special Technologies**

## **Environmental Specifications & Tests**

NSF 140:	N/A Certified
<b>Total Recycled Content</b>	0%
<b>Flooring Radiant Panel</b>	Class 1
Smoke Density	Less then 450.0 flaming (ASTM E 662)
Static Test	Less then 3.0 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



185 Fiesta



3124 Red



3130 Brown



2152 Tungsten



3125 Pewter




3131 Pecan



3120 Shadow



3126 Steel



316 Royal



3121 Charcoal



3127 Noir




860 London Fog



3122 Denim



3128 Licorice



997 Caviar



3123 Praline



3129 Ash

