



Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	15 oz./sy (509 grams/m2)
Pile Density	5133 oz./y3 (190.33 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT APEX® SDP Polyester Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs

Special Technologies

Environmental Specifications & Tests


NSF 140:	Gold Certified
Total Recycled Content	76.4%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Quarter Turn, Monolithic, Ashlar


Colorways




185 Fiesta




2152 Tungsten



3120 Shadow




3121 Charcoal



3122 Denim




3123 Praline




3124 Red



3125 Pewter




3126 Steel




3128 Licorice




3129 Ash



3130 Brown




3131 Pecan



316 Royal



860 London Fog



997 Caviar