



Product Specifications

Construction	Textured Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	13 oz./sy (441 grams/m2)
Pile Density	4431 oz./y3 (164.30 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Standard Back APEX® SDP Polyester Fiber
Optional Warranties	Tile Tabs

Special Technologies

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




185 Fiesta



3120 Shadow




3121 Charcoal




3122 Denim



3123 Praline




3124 Red



3125 Pewter



3126 Steel



3128 Licorice




3129 Ash



3130 Brown




3131 Pecan



316 Royal



860 London Fog



997 Caviar