





Installation Methods: Brick, Quarter Turn, Monolithic, Ashlar


Colorways




3388 Certainty




3389 Matter of ...




3390 Cold Hard ...




3391 Done Deal




3392 Fact of Life




3393 Sure Thing



3394 All Sewn Up



3395 Sure Bet



3396 Shoo-In

Product Specifications

| | |
|----------------------------|---|
| Backing | Nexus® Modular |
| Dye Method | Solution Dyed |
| Fiber Type | APEX SDP® Polyester |
| Face Weight | 20 oz./sy (678 grams/m2) |
| Pile Density | 5414 oz./y3 (200.75 kg/m3) |
| Pattern Repeat | N/A |
| Gauge | 1/12 (4.72 rows/cm) |
| Standard Size | 24" x 24" approx. (60.96cm x 60.96cm) |
| Standard Adhesive | Commercialon Premium Modular Adhesive |
| Optional Adhesive | TileTabs |
| Standard Warranties | Nexus Modular Commercialon Adhesive for Modular Carpet & LVT APEX® SDP Polyester Fiber |
| Optional Warranties | Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs |

Special Technologies

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 71.4% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 4 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |